NSN 5985-01-339-5154

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-339-5154

Application Design:

Transmission line

Body Material:

Copper alloy

Body Style:

Err-090

Body Surface Treatment:

Any acceptable

Overall Length:

0.870 inches

Overall Diameter:

Between 0.260 inches and 0.300 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.15

Input Impedance Rating In Ohms:

. 50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average and 500.0 watts peak

Rf Signal Attenuation In Decibels:

2.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+2.0 gigahertz

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 2.000 gigahertz

Test Data Document:

81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-a-3933/25 government specification

Fsc Application Data:

Antennas, waveguide and related equipment

NSN 5985-01-339-5154

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A20000

