## NSN 5985-01-340-8758

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-340-8758 **Application Design:** Transmission line **Body Material:** Metal and plastic **Body Style:** Rectangular terminal/terminals on one surface **Terminal Material:** Copper **Terminal Surface Treatment:** Nickel plated and silver plated **Body Surface Treatment:** Nickel plated **Overall Length:** 0.800 inches **Overall Height:** 0.125 inches **Overall Width:** 0.710 inches **Mounting Hole/stud Quantity: Unthreaded Mounting Hole Diameter:** 0.125 inches **Operating Tempurature Range:** -55.0/+100.0 degrees celsius **End Application:** An/sps-40d **Voltage Standing Wave Ratio:** 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Power Rating:** 40.0 watts average Rf Signal Attenuation In Decibels: **Voltage Standing Wave Ratio Frequency Range:** +0.0/+0.5 gigahertz **Attenuation Accuracy In Decibels:** 

-0.50/+0.50

Mounting Method:

Mounting Method
Unthreaded hole

## NSN 5985-01-340-8758

Fixed Attenuator - Page 2 of 2



Terminal Type And Quantity:
3 surface contact
Frequency Range:
Between 0.000 hertz and 0.500 gigahertz
Precious Material And Location:
Terminals silver
Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A20000