# NSN 5985-01-340-8759

Fixed Attenuator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5985-01-340-8759

## Application Design: Transmission line

Body Material:

Metal and plastic

Body Style:

Rectangular terminal/terminals on three surfaces

## **Body Surface Treatment:**

Painted

Overall Length:

0.370 inches

**Overall Height:** 

0.055 inches

### **Overall Width:**

0.245 inches

### End Application:

### An/sps-40d radar set

Voltage Standing Wave Ratio:

1.30

#### Input Impedance Rating In Ohms:

50.0

## Output Impedance Rating In Ohms:

50.0

#### **Power Rating:**

1.0 watts average and 100.0 watts peak

## Rf Signal Attenuation In Decibels:

15.0

## Voltage Standing Wave Ratio Frequency Range:

+0.0/+1.0 gigahertz

## Attenuation Accuracy In Decibels:

-0.50/+0.50

#### **Mounting Method:**

Printed circuit

#### **Terminal Type And Quantity:**

3 surface contact

#### Frequency Range:

Between 0.000 hertz and 1.000 gigahertz

## **Special Features:**

Dust from item when machined, abrade, filed or cut is hazardous

#### **Precious Material And Location:**

Contact surfaces platinum and contact surfaces silver

#### **Precious Material:**

Platinum and silver

# NSN 5985-01-340-8759

Fixed Attenuator - Page 2 of 2



**Fsc Application Data:** 

Antennas, waveguides, and related equip.

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A20000