## NSN 5985-01-340-8760

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-340-8760

Application Design:
Transmission line
Body Material:
Metal and plastic
Body Style:
Rectangular terminal/terminals on three surfaces
Overall Length:
0.625 inches
Overall Height:
0.150 inches
Overall Width:
0.515 inches
Mounting Hole/stud Quantity:
1
Unthreaded Mounting Hole Diameter:
0.116 inches
Operating Tempurature Range:
-55.0/+150.0 degrees celsius
Voltage Standing Wave Ratio:
1.15
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
20.0 watts average
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Mounting Method:
Unthreaded hole
Terminal Type And Quantity:
3 surface contact
Frequency Range:
Between 0.000 hertz and 4.000 gigahertz
Special Features:
This device incorporates beryllium oxide, the dust of which is toxic
Shelf Life:

N/a

## NSN 5985-01-340-8760

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A20000