NSN 5985-01-341-2358

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-341-2358

Application Design:
Transmission line
Body Material:
Brass
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
1.040 inches
Overall Diameter:
0.400 inches
Voltage Standing Wave Ratio:
1.15 and 1.30 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Rf Signal Attenuation In Decibels:
11.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-1.00/+1.00
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
0.500 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Specification Data:
14482-632675 manufacturers source control
Fsc Application Data:

1 30 Application Data

Antennas, waveguides, and related equip.

NSN 5985-01-341-2358

Fixed Attenuator - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000