

View Online at <https://aerobasegroup.com/nsn/5985-01-341-6564>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches all flanges and 1.006 inches all flanges

Flange Inside Height:

0.503 inches all flanges and 0.506 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Maximum Operating Pressure:

60.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Special Features:

Frequency range 12.4 to 18.0 ghz

Flexibility:

Flexible single tubing segment

Material:

Rubber synthetic single tubing jacket

Surface Treatment:

Any acceptable all flange outside surfaces

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0