

View Online at <https://aerobasegroup.com/nsn/5985-01-342-3412>

Cross Sectional Shape:

Internal, rectangular double ridged external, rectangular double indented

Thread Class:

2b first flange first connection facility

Thread Direction:

Right-hand first flange first connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Straight twist single tubing segment

Tubing Twist Angle In Deg:

90.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.688 inches all flanges and 0.694 inches all flanges

Flange Inside Height:

0.318 inches all flanges and 0.324 inches all flanges

Flange Outside Width:

1.360 inches all flanges and 1.390 inches all flanges

Flange Outside Height:

1.360 inches all flanges and 1.390 inches all flanges

Flange Depth:

0.235 inches all flanges and 0.265 inches all flanges

Flange Connecting Hole Diameter:

0.145 inches first flange second connection facility and 0.148 inches first flange second connection facility

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.15

Thready Qty Per Inch (tpi):

32 first flange first connection facility

Waveguide Outside Width:

Between 0.788 inches and 0.794 inches

Thread Size:

0.138 inches first flange first connection facility

Waveguide Inside Width:

Between 0.688 inches and 0.694 inches

Waveguide Inside Height:

Between 0.318 inches and 0.324 inches

Waveguide Outside Height:

Between 0.418 inches and 0.424 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Contact, double ridge type all flanges

Waveguide Length:

Between 1.990 inches and 2.010 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange first connection facility

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0