NSN 5985-01-342-3446

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-342-3446
Application Design:
Transmission line
Body Material:
Steel, corrosion resisting
Body Style:
1b round, terminal/terminals in opposite surface
Terminal Material:
Steel, corrosion resisting
Terminal Surface Treatment:
Passivated, qq-p-35
Body Surface Treatment:
Passivated, qq-p-35
Overall Length:
1.240 inches
Overall Diameter:
0.390 inches
Operating Tempurature Range:
-54.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.30 and 1.35
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 0.2 kilowatts peak
Rf Signal Attenuation In Decibels:
2.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.40/+0.40
Connection Type Per Function:
Female output and male input
Unpackaged Unit Weight:
0.500 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-01-342-3446

Fixed Attenuator - Page 2 of 2



he		

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000