## NSN 5985-01-342-8405

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-342-8405

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
2.010 inches
Overall Height:
0.300 inches
Overall Width:
1.630 inches
Unthreaded Mounting Hole Diameter:
0.104 inches
Distance Between Mounting Facility Centers:
1.050 inches
Voltage Standing Wave Ratio:
1.80
Coaxial Connector Series Designation:
Sma
Power Rating:
100.0 milliwatts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.5
2.5  Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +10.0/+60.0
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method:
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity:
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity: 5
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity: 5 Attenuation Per Step In Decibels:
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity: 5 Attenuation Per Step In Decibels: 10.0
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity: 5 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity:
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity: 5 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 unthreaded hole
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity: 5 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range:
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity: 5 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 6.000 gigahertz and 18.000 gigahertz
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity: 5 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 6.000 gigahertz and 18.000 gigahertz Segment Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity: 5 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 6.000 gigahertz and 18.000 gigahertz Segment Attenuation Range In Decibels: +0.00/+10.00 and +10.00/+20.00 and +20.00/+40.00 and +40.00/+60.00
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity: 5 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 6.000 gigahertz and 18.000 gigahertz Segment Attenuation Range In Decibels: +0.00/+10.00 and +10.00/+20.00 and +20.00/+40.00 and +40.00/+60.00 Adjustment Device Type And Quantity:
Overall Attenuation Range In Decibels: +10.0/+60.0 Attenuation Variation Method: Stepped Step Position Quantity: 5 Attenuation Per Step In Decibels: 10.0 Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 6.000 gigahertz and 18.000 gigahertz Segment Attenuation Range In Decibels: +0.00/+10.00 and +10.00/+20.00 and +20.00/+40.00 and +40.00/+60.00 Adjustment Device Type And Quantity: 1 electronic, current controlled
Overall Attenuation Range In Decibels: +10.0/+60.0  Attenuation Variation Method: Stepped Step Position Quantity: 5  Attenuation Per Step In Decibels: 10.0  Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 6.000 gigahertz and 18.000 gigahertz  Segment Attenuation Range In Decibels: +0.00/+10.00 and +10.00/+20.00 and +20.00/+40.00 and +40.00/+60.00  Adjustment Device Type And Quantity: 1 electronic, current controlled Terminal Type And Quantity:

## NSN 5985-01-342-8405

Variable Attenuator - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0