NSN 5985-01-343-3622

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-343-3622

Cross Sectional Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

42.5 single bend e-plane

Tubing Wall Construction Style:

Corrugated single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Tubing Twist Angle In Deg:

85.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches all flanges and 1.006 inches all flanges

Flange Inside Height:

0.503 inches all flanges and 0.506 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.20

Insertion Loss In Decibels:

0.20

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

NSN 5985-01-343-3622 Waveguide Assembly - Page 2 of 2



Waveguide Length:
23.000 inches
Special Features:
Frequency range 8.5 to 9.6 ghz
Flexibility:
Flexible single tubing segment
Material:
Copper alloy all tubing segment and flange
Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver all tubing segment and flange inside surfaces
Style Designator:
Straight type
Fsc Application Data:
Antennas, waveguides, and related equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A073a0