## NSN 5985-01-343-3653

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-343-3653

| Application Design:  |
|--|
| Printed circuit board                                      |
| Body Style:  |
| Rectangular, terminals on one surface                      |
| Overall Length:  |
| 0.827 inches   |
| Overall Height:  |
| 0.420 inches   |
| Overall Width:   |
| 0.627 inches   |
| Voltage Standing Wave Ratio:                               |
| 1.40   |
| Insertion Loss At Minimum Attenuation In Maximum Decibels: |
| 2.0  |
| Overall Attenuation Range In Decibels:                     |
| +0.0/+27.0   |
| Attenuation Variation Method:                              |
| Stepped  |
| Step Position Quantity:                                    |
| 3  |
| Attenuation Per Step In Decibels:                          |
| 3.0 and 21.0 and 3.0                                       |
| Mounting Facility Type And Quantity:                       |
| 15 terminal  |
| Frequency Range:   |
| Between 520.000 megahertz and 560.000 megahertz            |
| Adjustment Device Type And Quantity:                       |
| 1 electronic, programmable                                 |
| Impedance Rating In Ohms:                                  |
| 50.0 input-output  |
| Precious Material And Location:                            |
| Pin surface gold   |
| Precious Material:   |
| Gold   |
| Terminal Type And Quantity:                                |
| 15 pin   |
| Fsc Application Data:                                      |
| Antennas, waveguides and related equipment                 |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

--

## NSN 5985-01-343-3653

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0