# NSN 5985-01-343-3653

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-343-3653

# Application Design:

Printed circuit board

#### Body Style:

Rectangular, terminals on one surface

# **Overall Length:**

0.827 inches

#### **Overall Height:**

0.420 inches

#### **Overall Width:**

0.627 inches

# Voltage Standing Wave Ratio:

1.40

# Insertion Loss At Minimum Attenuation In Maximum Decibels:

2.0

# **Overall Attenuation Range In Decibels:**

+0.0/+27.0

# Attenuation Variation Method:

Stepped

# **Step Position Quantity:**

3

# Attenuation Per Step In Decibels:

3.0 and 21.0 and 3.0

# Mounting Facility Type And Quantity:

15 terminal

#### **Frequency Range:**

Between 520.000 megahertz and 560.000 megahertz

# Adjustment Device Type And Quantity:

1 electronic, programmable

#### Impedance Rating In Ohms:

50.0 input-output

#### **Precious Material And Location:**

Pin surface gold

#### **Precious Material:**

Gold

# **Terminal Type And Quantity:**

15 pin

#### Fsc Application Data:

Antennas, waveguides and related equipment

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5985-01-343-3653

Variable Attenuator - Page 2 of 2

Demilitarization:

No

Fiig:

A223a0

