## NSN 5985-01-343-3654

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-343-3654

Application Design:
Printed circuit board
Body Style:
Rectangular, terminals on one surface
Overall Length:
0.827 inches
Overall Height:
0.400 inches
Overall Width:
0.627 inches
Voltage Standing Wave Ratio:
1.40
Insertion Loss At Minimum Attenuation In Maximum Decibels:
2.0
Overall Attenuation Range In Decibels:
+0.0/+18.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
3
Attenuation Per Step In Decibels:
6.0
Mounting Facility Type And Quantity:
15 terminal
Frequency Range:
Between 520.000 megahertz and 560.000 megahertz
Adjustment Device Type And Quantity:
1 electronic, programmable
Impedance Rating In Ohms:
50.0 input-output
Precious Material And Location:
Pin surface gold
Precious Material:
Gold
Terminal Type And Quantity:
15 pin
Fsc Application Data:
Antennas, waveguides and related equipment
Shelf Life:
N/a
Unit Of Measure:
Unit Of Measure:

--

## NSN 5985-01-343-3654

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0