NSN 5985-01-344-0176

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-344-0176

| Application Design: |
|---|
| Printed circuit board |
| Body Style: |
| Rectangular, terminals on one surface |
| Overall Length: |
| 1.350 inches |
| Overall Height: |
| 0.750 inches |
| Overall Width: |
| 0.800 inches |
| Shaft Diameter: |
| Between 0.120 inches and 0.130 inches |
| Shaft Length: |
| 0.600 inches |
| Voltage Standing Wave Ratio: |
| 1.50 |
| Power Rating: |
| 0.5 watts average |
| Overall Attenuation Range In Decibels: |
| +0.0/+15.0 |
| Attenuation Variation Method: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 1 printed circuit |
| Frequency Range: |
| Between 0.000 hertz and 250.000 megahertz |
| Overall Attenuation Accuracy In Decibels: |
| -0.20/+0.20 |
| Adjustment Device Type And Quantity: |
| 1 shaft |
| Shaft Type: |
| Round, slotted |
| Impedance Rating In Ohms: |
| 50.0 input-output |
| Precious Material And Location: |
| External surfaces gold |
| Precious Material: |
| Gold |
| Terminal Type And Quantity: |
| 4 pin |
| Shelf Life: |
| N/a |

NSN 5985-01-344-0176

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0