NSN 5985-01-344-4686

Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-344-4686

Body Style:
Rectangular
Overall Length:
1.750 inches
Overall Height:
0.780 inches
Overall Width:
1.750 inches
Frequency Rating:
2.5 gigahertz single frequency voltage standing wave ratio and 4.0 gigahertz single frequency voltage standing wave ratio
Unthreaded Mounting Hole Diameter:
0.102 inches
Switch Type:
Nontransfer
Longest Horizontal Distance Between Mounting Centers:
1.200 inches single mounting facility pattern
Shortest Horizontal Distance Between Mounting Centers:
0.800 inches single mounting facility pattern
Operating Tempurature Range:
-54.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.50 single
Insertion Loss In Decibels:
1.10 single
Coaxial Connector Series Designation:
Sma
Connector End Design:
Female
Rf Power Handling Capability:
0.02 watts average single
Minimum Crosstalk Rating In Decibels:
75.0 single
Actuator Operating Method:
Solid state
Actuator Current Type And Rating In Amps:
Between 0.05 dc and 0.1 dc
Actuator Voltage In Volts:
Between 0.8 and 2.7
Switch Operation Sequence:

Switching Time:

Breaks before makes

100.0 microseconds

NSN 5985-01-344-4686

Radio Frequency Transmission Line Switch - Page 2 of 2



Pole Quantity:
1
Throw Quantity:
3
Coupling Position Quantity:
4
Mounting Facility Type And Quantity:
4 unthreaded hole
Mounting Facility Pattern:
Four position rectangular single mounting facility pattern
Material:
Steel body
Terminal Type And Quantity:
4 connector, receptacle and 6 solder stud
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A158a0