## NSN 5985-01-345-0746

Variable Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-345-0746 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** 2.500 inches **Overall Height:** 2.000 inches **Overall Width:** 0.560 inches **End Application:** Afscn/cue **Voltage Standing Wave Ratio:** 1.50 **Power Rating:** 5.0 watts average **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.5 **Overall Attenuation Range In Decibels:** +0.0/+10.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 unthreaded hole Frequency Range: Between 2.000 gigahertz and 4.000 gigahertz **Overall Attenuation Accuracy In Decibels:** -1.00/+1.00 **Special Features:** Body, aluminum; connector, stainless steel; resettability, 0.1 db or less; temp., operating, +16 to +40 deg. C.; non-operating, minus 42 deg. To +52 deg.C.; humidity, operating, 30 to 70% relative noncondensing; nonoperating, up to 100% (including condensation due to temperature changes) at temperatures up to +40 deg.C. **Terminal Type And Quantity:** 3 connector, coaxial, male Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A223a0

No