## NSN 5985-01-345-5024

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-345-5024

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange all connection facilities

**Thread Direction:** 

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.620 inches first flange and 0.624 inches first flange

Flange Inside Height:

0.309 inches first flange and 0.313 inches first flange

Flange Outside Width:

1.297 inches first flange and 1.327 inches first flange

Flange Outside Height:

1.297 inches first flange and 1.327 inches first flange

Flange Inside Diameter:

0.985 inches first flange and 1.015 inches first flange

Flange Depth:

0.360 inches first flange and 0.390 inches first flange

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

**Waveguide Outside Width:** 

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.619 inches and 0.624 inches

Waveguide Inside Height:

Between 0.308 inches and 0.313 inches

**Waveguide Outside Height:** 

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

Flange Style:

Choke type first flange

Flexibility:

Rigid single tubing segment

Material:

Aluminum all tubing segment and flange

## NSN 5985-01-345-5024

Waveguide Assembly - Page 2 of 2



^		-			
SII	rface	ıre	atm	ent	۰

Enamel all tubing segment and flange outside surfaces

**Thread Series Designator:** 

Unc first flange all connection facilities

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A073a0