## NSN 5985-01-347-5506

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-347-5506

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.760 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.750 inches
Overall Height:
0.900 inches
Overall Width:
1.500 inches
Coaxial Connector Series Designation:
Wpm
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+32.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
Attenuation Per Step In Decibels:
0.25 and 0.5 and 1.0 and 2.0 and 4.0 and 8.0 and 16.0
Mounting Facility Type And Quantity:
6 threaded hole
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
1 electronic, programmable
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.112 inches
Terminal Type And Quantity:
2 connector, coaxial, female and 9 wire lead
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5985-01-347-5506

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0