NSN 5985-01-348-4388

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:



View Online at https://aerobasegroup.com/nsn/5985-01-348-4388

Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Passivated
Overall Length:
0.860 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-13.0/+30.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
2.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz
Shelf Life:
N/a
Unit Of Measure:

NSN 5985-01-348-4388

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000