NSN 5985-01-349-5785

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-349-5785

Application Design.
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
Between 2.025 inches and 2.145 inches
Overall Height:
Between 1.567 inches and 1.587 inches
Overall Width:
Between 1.177 inches and 1.197 inches
End Application:
5895-01-166-6949 display board, combat information central
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average and 100.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.3
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
Attenuation Per Step In Decibels:
10.0
Frequency Range:
Between 0.000 hertz and 2.500 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.30/+0.30
Adjustment Device Type And Quantity:
1 knob w/dial
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5985-01-349-5785

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0