NSN 5985-01-353-5566

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-353-5566

Application Design:
Transmission line
Body Material:
Copper alloy
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
3.490 inches
Overall Diameter:
1.650 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
Radar, search, an/sps-40
Voltage Standing Wave Ratio:
1.15
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
20.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Male input and female output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:

Feat

Between 0.000 hertz and 4.000 gigahertz

Criticality Code Justification:

NSN 5985-01-353-5566

Fixed Attenuator - Page 2 of 2



Sı	oec	ial	Fe	atı	ur	es	:
----	-----	-----	----	-----	----	----	---

Weapon system essential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000