NSN 5985-01-353-7992



Fixed Attenuator - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5985-01-353-7992
Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Terminal Material:
Steel, stainless
Terminal Surface Treatment:
Passivated
Body Surface Treatment:
Any acceptable
Overall Length:
0.860 inches
Overall Height:
Between 0.292 inches and 0.332 inches
Overall Width:
Between 0.292 inches and 0.332 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.07
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
4.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+8.0 gigahertz

Attenuation Accuracy In Decibels:

-0.30/+0.30

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 8.000 gigahertz

Fsc Application Data:

Antennas, waveguides and related equip.

NSN 5985-01-353-7992

Fixed Attenuator - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000