NSN 5985-01-355-4681

Waveguide Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-355-4681

| Internal, rectangular external, rectangular Bend Angle In Deg: 90.0 all bends e-plane End Application: An/apq-175 Flange Quantity: 2 Voltage Standing Wave Ratio: 1.05 |
|--|
| 90.0 all bends e-plane End Application: An/apq-175 Flange Quantity: 2 Voltage Standing Wave Ratio: |
| End Application: An/apq-175 Flange Quantity: 2 Voltage Standing Wave Ratio: |
| An/apq-175 Flange Quantity: 2 Voltage Standing Wave Ratio: |
| Flange Quantity: 2 Voltage Standing Wave Ratio: |
| 2 Voltage Standing Wave Ratio: |
| Voltage Standing Wave Ratio: |
| |
| 1.05 |
| |
| Insertion Loss In Decibels: |
| 0.15 |
| Flange Style: |
| Choke type all flanges |
| Waveguide Center To Center Distance: |
| 6.840 inches |
| Special Features: |
| Freq.Range, 9.00 to 9.60 ghz |
| Flexibility: |
| Rigid single tubing segment |
| Material: |
| Aluminum all tubing segment and flange |
| Surface Treatment: |
| Primer all tubing segment and flange all surfaces and paint all tubing segment and flange all surfaces |
| Style Designator: |
| Double bend type |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A073a0 |
| |