NSN 5985-01-356-8597

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-356-8597

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

3.900 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches

Overall Height:

1.260 inches

Overall Width:

1.460 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

End Application:

6625-01-244-3469 calibrator frequency

Voltage Standing Wave Ratio:

1.20

Coaxial Connector Series Designation:

Sma

Power Rating:

100.0 milliwatts average

Insertion Loss At Minimum Attenuation In Maximum Decibels:

1.5

Overall Attenuation Range In Decibels:

+0.0/+63.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

6

Attenuation Per Step In Decibels:

1.0 and 2.0 and 4.0 and 8.0 and 16.0 and 32.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 0.000 hertz and 500.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.60/+0.60

Adjustment Device Type And Quantity:

1 electronic, programmable

NSN 5985-01-356-8597

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern: Four position rectangular

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female and 7 pin and 1 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0