NSN 5985-01-356-8597

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-356-8597

3
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.900 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.000 inches
Overall Height:
1.260 inches
Overall Width:
1.460 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
End Application:
6625-01-244-3469 calibrator frequency
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Sma
Power Rating:
100.0 milliwatts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.5
Overall Attenuation Range In Decibels:
+0.0/+63.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
6
Attenuation Per Step In Decibels:
1.0 and 2.0 and 4.0 and 8.0 and 16.0 and 32.0
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 0.000 hertz and 500.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.60/+0.60
Adjustment Device Type And Quantity:

1 electronic, programmable

NSN 5985-01-356-8597

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female and 7 pin and 1 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A223a0