NSN 5985-01-357-2399

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-357-2399

Application Design:

Transmission line

Body Material:

Steel

Body Style:

Err-090

Body Surface Treatment:

Passivated

Overall Length:

0.860 inches

Operating Tempurature Range:

-54.0/+125.0 degrees celsius

End Application:

6625-01-271-4942 test set, radio

Voltage Standing Wave Ratio:

1.20

Input Impedance Rating In Ohms:

. 50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average and 100.0 watts peak

Rf Signal Attenuation In Decibels:

3.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+8.0 gigahertz

Attenuation Accuracy In Decibels:

-0.30/+0.30

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 8.000 gigahertz

Precious Material And Location:

Center contact gold

Precious Material:

Gold

Shelf Life:

N/a

NSN 5985-01-357-2399

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A20000

