## NSN 5985-01-357-2399

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-357-2399 **Application Design:** Transmission line **Body Material:** Steel **Body Style:** Err-090 **Body Surface Treatment:** Passivated **Overall Length:** 0.860 inches **Operating Tempurature Range:** -54.0/+125.0 degrees celsius **End Application:** 6625-01-271-4942 test set, radio **Voltage Standing Wave Ratio:** 1.20 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average and 100.0 watts peak **Rf Signal Attenuation In Decibels:** 3.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+8.0 gigahertz **Attenuation Accuracy In Decibels:** -0.30/+0.30 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 8.000 gigahertz **Precious Material And Location:** Center contact gold **Precious Material:** Gold Shelf Life:

N/a

## NSN 5985-01-357-2399

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000