NSN 5985-01-358-8570

Fixed Attenuator - Page 1 of 2



Tixed / (iteliaator Tage Tot 2	arvup
View Online at https://aerobasegroup.com/nsn/5985-01-358-8570	
Application Design:	
Transmission line	
Body Material:	
Aluminum alloy and copper alloy	
Body Style:	
Rectangular terminal/terminals on three surfaces	
Body Surface Treatment:	
Gold plated	
Overall Length:	
0.650 inches	
Overall Height:	
0.040 inches	
Overall Width:	
0.375 inches	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
End Application:	
An/alr-62 radar set	
Voltage Standing Wave Ratio:	
1.25 and 1.50	
Input Impedance Rating In Ohms:	
50.0	
Output Impedance Rating In Ohms:	
50.0	
Rf Signal Attenuation In Decibels:	
6.0	
Voltage Standing Wave Ratio Frequency Range:	
+0.0/+12.0 gigahertz	
Attenuation Accuracy In Decibels:	
-0.50/+0.50	
Mounting Method:	
Printed circuit	
Terminal Type And Quantity:	

3 surface contact

Frequency Range:

Between 0.000 hertz and 12.000 hertz

Precious Material And Location:

External surfaces gold

Precious Material:

Gold

Fsc Application Data:

Antennas, waveguides, and related equip.

NSN 5985-01-358-8570

Fixed Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000