Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-361-7383

		_
Ap	plicatio	n Design:

Transmission line

**Body Material:** 

Aluminum alloy

Body Style:

Err-090

#### **Body Surface Treatment:**

Chromium plated

## **Overall Length:**

0.860 inches

**Overall Diameter:** 

0.280 inches

**Operating Tempurature Range:** 

-54.0/+90.0 degrees celsius

#### Voltage Standing Wave Ratio:

1.10 and 1.15 and 1.20 and 1.25 and 1.35

## Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

## **Coaxial Connector Series Designation:**

Sma

#### **Power Rating:**

500.0 milliwatts average

#### **Rf Signal Attenuation In Decibels:**

8.0

# Voltage Standing Wave Ratio Frequency Range:

+0.0/+2.0 gigahertz and +2.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz

#### Attenuation Accuracy In Decibels:

-0.40/+0.40

#### Mounting Method:

Connector

#### **Terminal Type And Quantity:**

2 connector

#### Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

## **Specification Data:**

15786-308928 manufacturers source control

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5985-01-361-7383

Fixed Attenuator - Page 2 of 2

Demilitarization:

No

Fiig:

A20000

