NSN 5985-01-363-3407

Fixed Attenuator - Page 1 of 2

Unthreaded hole



View Online at https://aerobasegroup.com/nsn/5985-01-363-3407

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Body Surface Treatment:
Any acceptable
Overall Length:
2.060 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.336 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.836 inches
Overall Height:
0.720 inches
Overall Width:
1.000 inches
Mounting Hole/stud Quantity:
4
Body Length:
1.500 inches
Unthreaded Mounting Hole Diameter:
0.093 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Rf Signal Attenuation In Decibels:
10.0
Attenuation Accuracy In Decibels:
-0.25/+0.25
Connection Type Per Function:
Female input and female output
Mounting Method:

NSN 5985-01-363-3407

Fixed Attenuator - Page 2 of 2

Fiig: A20000



Terminal Type And Quantity:
2 connector
Frequency Range:
Between 500.000 megahertz and 700.000 megahertz
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No