NSN 5985-01-363-3413

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-363-3413

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
1.600 inches
Overall Height:
1.500 inches
Overall Width:
0.560 inches
Distance Between Mounting Facility Centers:
0.840 inches
Voltage Standing Wave Ratio:
1.25 and 1.50 and 1.80 and 2.00
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+15.0/+18.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 2 threaded hole
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range:
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 800.000 megahertz
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 800.000 megahertz Mounting Thread Quantity:
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 800.000 megahertz Mounting Thread Quantity: 56 per inch
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 800.000 megahertz Mounting Thread Quantity: 56 per inch Adjustment Device Type And Quantity:
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 800.000 megahertz Mounting Thread Quantity: 56 per inch Adjustment Device Type And Quantity: 1 slotted screw
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 800.000 megahertz Mounting Thread Quantity: 56 per inch Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern:
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 800.000 megahertz Mounting Thread Quantity: 56 per inch Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern: Two position in-line
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 800.000 megahertz Mounting Thread Quantity: 56 per inch Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern: Two position in-line Mounting Facility Screw Thread Diameter:
Mounting Facility Type And Quantity: 2 threaded hole Frequency Range: Between 0.000 megahertz and 800.000 megahertz Mounting Thread Quantity: 56 per inch Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern: Two position in-line Mounting Facility Screw Thread Diameter: 0.086 inches

2b internal

NSN 5985-01-363-3413

Variable Attenuator - Page 2 of 2



Terminal Type A	and Quantity	/:
-----------------	--------------	-----------

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0