NSN 5985-01-363-6620

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-363-6620

Application Design:
Transmission line
Body Material:
Aluminum alloy
Body Style:
Rectangular terminal/terminals on opposite surfaces
Body Surface Treatment:
Gold plated
Overall Length:
0.748 inches
Overall Height:
0.124 inches
Overall Width:
0.241 inches
Voltage Standing Wave Ratio:
1.20 and 1.35 and 1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Rf Signal Attenuation In Decibels:
Rf Signal Attenuation In Decibels: 6.0
-
6.0
6.0 Mounting Method:
6.0 Mounting Method: Terminal
6.0 Mounting Method: Terminal Terminal Type And Quantity:
6.0 Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead
6.0 Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead Frequency Range:
6.0 Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead Frequency Range: Between 0.000 hertz and 12.000 gigahertz
6.0 Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead Frequency Range: Between 0.000 hertz and 12.000 gigahertz Precious Material And Location:
Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead Frequency Range: Between 0.000 hertz and 12.000 gigahertz Precious Material And Location: Body surface gold
Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead Frequency Range: Between 0.000 hertz and 12.000 gigahertz Precious Material And Location: Body surface gold Precious Material:
Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead Frequency Range: Between 0.000 hertz and 12.000 gigahertz Precious Material And Location: Body surface gold Precious Material: Gold
Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead Frequency Range: Between 0.000 hertz and 12.000 gigahertz Precious Material And Location: Body surface gold Precious Material: Gold Shelf Life:
Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead Frequency Range: Between 0.000 hertz and 12.000 gigahertz Precious Material And Location: Body surface gold Precious Material: Gold Shelf Life: N/a
Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead Frequency Range: Between 0.000 hertz and 12.000 gigahertz Precious Material And Location: Body surface gold Precious Material: Gold Shelf Life: N/a
Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead Frequency Range: Between 0.000 hertz and 12.000 gigahertz Precious Material And Location: Body surface gold Precious Material: Gold Shelf Life: N/a Unit Of Measure:
Mounting Method: Terminal Terminal Type And Quantity: 2 wire lead Frequency Range: Between 0.000 hertz and 12.000 gigahertz Precious Material And Location: Body surface gold Precious Material: Gold Shelf Life: N/a Unit Of Measure: Demilitarization: