

View Online at <https://aerobasegroup.com/nsn/5985-01-365-1361>

Body Style:

Rectangular

Overall Length:

2.380 inches

Overall Height:

3.200 inches

Overall Width:

0.900 inches

Frequency Rating:

0.0 gigahertz single frequency operating and 3.0 gigahertz single frequency operating
0.0 gigahertz single frequency rf power handling and 3.0 gigahertz single frequency rf power handling
0.0 gigahertz single frequency voltage standing wave ratio and 3.0 gigahertz single frequency voltage standing wave ratio
0.0 gigahertz single frequency insertion loss reference and 3.0 gigahertz single frequency insertion loss reference
0.0 gigahertz single frequency crosstalk reference and 3.0 gigahertz single frequency crosstalk reference

Unthreaded Mounting Hole Diameter:

0.147 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

2.500 inches single mounting facility pattern

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

0.20 single

Rf Power Handling Capability:

200.0 watts average single

Minimum Crosstalk Rating In Decibels:

80.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.2 dc

Actuator Voltage In Volts:

Between 24.0 and 30.0

Switch Operation Sequence:

Makes before breaks

Switching Time:

15.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Aluminum bodyberyllium contact (s) aluminum cover

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Surface Treatment:

Nickel body outside surfacesgold contact (s) outside surfacespaint cover outside surfaces

Terminal Type And Quantity:

3 quick disconnect, female and 1 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0