NSN 5985-01-365-1361

Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-365-1361 **Body Style:** Rectangular **Overall Length:** 2.380 inches **Overall Height:** 3.200 inches **Overall Width:** 0.900 inches Frequency Rating: 0.0 gigahertz single frequency operating and 3.0 gigahertz single frequency operating 0.0 gigahertz single frequency of power handling and 3.0 gigahertz single frequency rf power handling 0.0 gigahertz single frequency voltage standing wave ratio and 3.0 gigahertz single frequency voltage standing wave ratio 0.0 gigahertz single frequency insertion loss reference and 3.0 gigahertz single frequency insertion loss reference0.0 gigahertz single frequency crosstalk reference and 3.0 gigahertz single frequency crosstalk reference **Unthreaded Mounting Hole Diameter:** 0.147 inches **Switch Type:** Nontransfer **Distance Between Mounting Facility Centers:** 2.500 inches single mounting facility pattern **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Voltage Standing Wave Ratio:** 1.20 single **Insertion Loss In Decibels:** 0.20 single Rf Power Handling Capability: 200.0 watts average single Minimum Crosstalk Rating In Decibels: 80.0 single **Actuator Operating Method: Actuator Current Type And Rating In Amps:** 0.2 dc **Actuator Voltage In Volts:** Between 24.0 and 30.0 **Switch Operation Sequence:** Makes before breaks **Switching Time:** 15.0 milliseconds Switch Return Mechanism Type:

0

Fail-safe

Pole Quantity:

Throw Quantity:

NSN 5985-01-365-1361

Radio Frequency Transmission Line Switch - Page 2 of 2



Coupling Position Quantity:
4
Mounting Facility Type And Quantity:
2 unthreaded hole
Mounting Facility Pattern:
Two position in-line single mounting facility pattern
Material:
Aluminum bodyberyllium contact (s) aluminum cover
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Surface Treatment:
Nickel body outside surfacesgold contact (s) outside surfacespaint cover outside surfaces
Terminal Type And Quantity:
3 quick disconnect, female and 1 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A158a0