

View Online at <https://aerobasegroup.com/nsn/5985-01-365-5037>

Body Style:

Rectangular

Overall Length:

2.090 inches

Overall Height:

1.340 inches

Overall Width:

0.520 inches

Frequency Rating:

0.0 gigahertz 1st frequency crosstalk reference and 3.6 gigahertz 1st frequency crosstalk reference3.6 gigahertz 2nd frequency crosstalk reference and 19.0 gigahertz 2nd frequency crosstalk reference0.0 gigahertz single frequency operating and 19.0 gigahertz single frequency operating0.0 gigahertz single frequency voltage standing wave ratio and 19.0 gigahertz single frequency voltage standing wave ratio0.0 gigahertz single frequency insertion loss reference and 19.0 gigahertz single frequency insertion loss reference

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.105 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

0.440 inches single mounting facility pattern

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.50 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

80.0 1st60.0 2nd

Actuator Operating Method:

Solid state

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Aluminum alloy 6061 body stainless steel connecto (s) copper alloy terminal(s)

Unpackaged Unit Weight:

2.000 ounces

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Surface Treatment:

Chromate body all surfaces passivate connecto (s) outside surfaces gold terminal(s) outside surfaces

Terminal Type And Quantity:

1 connector, receptacle and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0