NSN 5985-01-367-9926

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-367-9926

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

Flange Outside Width:

2.070 inches all flanges and 2.110 inches all flanges

Flange Outside Height:

1.570 inches all flanges and 1.610 inches all flanges

Flange Depth:

0.480 inches all flanges and 0.520 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.171 inches all flanges all connection facilities

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Waveguide Longer Offset Distance:

4.171 inches

Flange Connecting Facility And Quantity:

10 unthreaded hole all flanges all connection facilities

Flange Style:

Contact type all flanges

Waveguide Offset Distance:

1.190 inches

Flexibility:

Rigid all tubing segment

Material:

Aluminum alloy all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

NSN 5985-01-367-9926

Waveguide Assembly - Page 2 of 2



Style Designator:
Bend type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A073a0