NSN 5985-01-368-1186

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-368-1186

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches first flange and 0.904 inches first flange

Flange Inside Height:

0.396 inches first flange and 0.404 inches first flange

Flange Outside Width:

1.610 inches first flange and 1.640 inches first flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.423 inches first flange and 0.453 inches first flange

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

1.000 inches and 1.250 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

0.900 inches and 1.122 inches

Waveguide Inside Height:

0.400 inches and 0.497 inches

Waveguide Outside Height:

0.500 inches and 0.625 inches

Waveguide Longer Offset Distance:

7.286 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

Flange Style:

Choke type first flange

Waveguide Offset Distance:

2.796 inches

Flexibility:

Rigid all tubing segment

Material:

Aluminum alloy all tubing segment and flange

NSN 5985-01-368-1186

Waveguide Assembly - Page 2 of 2



c.	ırfa	'	т.,		4	~ ~	٠.
Ðι	ırıa	ce	11	eа	ш	er	H.

Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

Style Designator:

Bend type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A073a0