

View Online at <https://aerobasegroup.com/nsn/5985-01-368-1193>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches second flange and 0.903 inches second flange

Flange Inside Height:

0.397 inches second flange and 0.403 inches second flange

Flange Outside Width:

2.070 inches second flange and 2.110 inches second flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.480 inches second flange and 0.520 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.171 inches second flange all connection facilities

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

0.996 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

Waveguide First Leg Length:

1.154 inches

Flange Style:

Contact type second flange

Waveguide Second Leg Length:

2.000 inches

Waveguide Third Leg Length:

10.000 inches

Waveguide Fourth Leg Length:

25.620 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

Style Designator:

Three bend type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A073a0