NSN 5985-01-368-1804

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-368-1804

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange and 1.256 inches second flange

Flange Inside Height:

0.628 inches second flange and 0.631 inches second flange

Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

Flange Depth:

0.423 inches second flange and 0.453 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

1.000 inches and 1.250 inches

Waveguide Inside Width:

0.900 inches and 1.122 inches

Waveguide Inside Height:

0.400 inches and 0.497 inches

Waveguide Outside Height:

0.500 inches and 0.625 inches

Waveguide Longer Offset Distance:

13.461 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Offset Distance:

5.838 inches

Flexibility:

Rigid all tubing segment

Material:

Aluminum alloy all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

NSN 5985-01-368-1804

Waveguide Assembly - Page 2 of 2



Style Designator:
Bend type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

No

A073a0