NSN 5985-01-368-2667

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-368-2667
Application Design:
Transmission line
Body Material:
Metal
Body Style:
Err-090
Overall Length:
1.240 inches
Overall Diameter:
Between 0.350 inches and 0.385 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.20 and 1.25 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 500.0 watts peak
Rf Signal Attenuation In Decibels:
16.0
Attenuation Accuracy In Decibels:
-0.70/+0.70
Connection Type Per Function:
Male input and female output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Special Features:
Vswr frequency ranges are 0.0 to 4.0 ghz, 4.0 to 8.0 ghz, 8.0 to 12.4 ghz, and 12.4 to 18.0 ghz
Test Data Document:
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-a-3933/16 government specification
Shelf Life:

N/a

NSN 5985-01-368-2667

Fixed Attenuator - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A20000