NSN 5985-01-368-2667

Fixed Attenuator - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5985-01-368-2667 |
|---|
| Application Design: |
| Transmission line |
| Body Material: |
| Metal |
| Body Style: |
| Err-090 |
| Overall Length: |
| 1.240 inches |
| Overall Diameter: |
| Between 0.350 inches and 0.385 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.15 and 1.20 and 1.25 and 1.35 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| Sma |
| Power Rating: |
| 2.0 watts average and 500.0 watts peak |
| Rf Signal Attenuation In Decibels: |
| 16.0 |
| Attenuation Accuracy In Decibels: |
| -0.70/+0.70 |
| Connection Type Per Function: |
| Male input and female output |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 18.000 gigahertz |
| Special Features: |
| Vswr frequency ranges are 0.0 to 4.0 ghz, 4.0 to 8.0 ghz, 8.0 to 12.4 ghz, and 12.4 to 18.0 ghz |
| Test Data Document: |
| 81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-a-3933/16 government specification |
| Shelf Life: |

N/a

NSN 5985-01-368-2667

Fixed Attenuator - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A20000