

View Online at <https://aerobasegroup.com/nsn/5985-01-368-3133>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Tubing Wall Construction Style:**

Seamless all tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.896 inches first flange and 0.904 inches first flange

**Flange Inside Height:**

0.396 inches first flange and 0.404 inches first flange

**Flange Outside Width:**

1.610 inches first flange and 1.640 inches first flange

**Flange Outside Height:**

1.610 inches first flange and 1.640 inches first flange

**Flange Depth:**

0.423 inches first flange and 0.453 inches first flange

**Flange Connecting Hole Diameter:**

0.169 inches first flange all connection facilities and 0.172 inches first flange all connection facilities

**Maximum Operating Pressure:**

15.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

**Waveguide Inside Width:**

Between 0.896 inches and 0.904 inches

**Waveguide Inside Height:**

Between 0.396 inches and 0.404 inches

**Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole first flange all connection facilities

**Flange Style:**

Cover type first flange

**Waveguide Leg Length:**

2.000 inches

**Waveguide Longer Leg Length:**

3.290 inches

**Waveguide Center To Center Distance:**

1.250 inches

**Flexibility:**

Rigid all tubing segment

**Material:**

Aluminum alloy all tubing segment and flange

**Surface Treatment:**

Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

**Style Designator:**

U-bend type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A073a0