

View Online at <https://aerobasegroup.com/nsn/5985-01-368-3783>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.118 inches first flange and 1.126 inches first flange

Flange Inside Height:

0.493 inches first flange and 0.501 inches first flange

Flange Outside Width:

1.860 inches first flange and 1.890 inches first flange

Flange Outside Height:

1.860 inches first flange and 1.890 inches first flange

Flange Depth:

0.610 inches first flange and 0.640 inches first flange

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

Waveguide First Leg Length:

1.406 inches

Flange Style:

Choke type first flange

Waveguide Second Leg Length:

2.720 inches

Waveguide Third Leg Length:

2.500 inches

Waveguide Fourth Leg Length:

1.220 inches

Flexibility:

Rigid all tubing segment

Material:

Aluminum alloy all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

Style Designator:

Three bend type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A073a0