# NSN 5985-01-368-5196

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-368-5196

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange all connection facilities

**Thread Direction:** 

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

#### Flange Inside Width:

0.896 inches second flange and 0.904 inches second flange

#### Flange Inside Height:

0.396 inches second flange and 0.404 inches second flange

### Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

# Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

#### Flange Depth:

0.610 inches second flange and 0.640 inches second flange

# Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

#### **Maximum Operating Pressure:**

15.0 pounds per square inch gage

#### **Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

# Thread Size:

0.164 inches first flange all connection facilities

#### **Waveguide Inside Width:**

Between 0.896 inches and 0.904 inches

# Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

# **Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

# Flange Style:

Choke type first flange

# Waveguide Second Leg Length:

5.190 inches

### Flexibility:

Rigid single tubing segment

# NSN 5985-01-368-5196

Waveguide Assembly - Page 2 of 2



Aluminum alloy all tubing segment and flange
Surface Treatment:
Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces
Style Designator:
Three bend type
Thread Series Designator:
Unc first flange all connection facilities
Shelf Life:

Demilitarization:

**Unit Of Measure:** 

No

N/a

Fiig:

A073a0

Material: