# NSN 5985-01-368-8952

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-368-8952

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### **Thread Class:**

2b first flange all connection facilities

#### **Thread Direction:**

Right-hand first flange all connection facilities

#### Flange Quantity:

2

#### Flange Inside Width:

0.896 inches first flange and 0.904 inches first flange

#### Flange Inside Height:

0.396 inches first flange and 0.404 inches first flange

#### Flange Outside Width:

1.610 inches first flange and 1.640 inches first flange

#### Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

#### Flange Depth:

0.423 inches first flange and 0.453 inches first flange

#### Maximum Operating Pressure:

15.0 pounds per square inch gage

## Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches first flange all connection facilities

#### Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

#### Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

## Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

## Waveguide Longer Offset Distance:

2.042 inches

## Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

#### Flange Style:

Choke type first flange

## Waveguide Offset Distance:

0.909 inches

Flexibility:

Rigid all tubing segment

#### Material:

Aluminum alloy all tubing segment and flange

# NSN 5985-01-368-8952

Waveguide Assembly - Page 2 of 2



## Surface Treatment:

Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

Style Designator:

Bend type

## Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A073a0