

View Online at <https://aerobasegroup.com/nsn/5985-01-368-8959>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches all flanges and 0.904 inches all flanges

Flange Inside Height:

0.396 inches all flanges and 0.404 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches all flanges all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges all connection facilities

Flange Style:

Choke type all flanges

Waveguide Leg Length:

1.220 inches

Waveguide Center To Center Distance:

1.750 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange outside surfaces and paint all tubing segment and flange outside surfaces

Style Designator:

U-bend type

Thread Series Designator:

Unc all flanges all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A073a0