

View Online at <https://aerobasegroup.com/nsn/5985-01-369-6516>

**Body Style:**

Rectangular

**Overall Length:**

2.645 inches

**Overall Height:**

2.750 inches

**Overall Width:**

3.750 inches

**Frequency Rating:**

0.0 gigahertz single frequency operating and 3.0 gigahertz single frequency operating

**Unthreaded Mounting Hole Diameter:**

0.170 inches

**Switch Type:**

Nontransfer

**Longest Horizontal Distance Between Mounting Centers:**

3.250 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

2.250 inches single mounting facility pattern

**Voltage Standing Wave Ratio:**

1.20 single

**Insertion Loss In Decibels:**

0.20 single

**Coaxial Connector Series Designation:**

Sma

**Rf Power Handling Capability:**

50.0 watts average single

**Minimum Crosstalk Rating In Decibels:**

80.0 single

**Actuator Operating Method:**

Manual

**Switch Operation Sequence:**

Breaks before makes

**Pole Quantity:**

1

**Throw Quantity:**

10

**Coupling Position Quantity:**

10

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Mounting Facility Pattern:**

Four position rectangular single mounting facility pattern

**Material:**

Aluminum alloy 6061 bodystainless steel connecto (s) aluminum cover

**Precious Material And Location:**

Connectors surface gold

**Precious Material:**

Gold

**Surface Treatment:**

Nickel body all surfacespassivate connecto (s) all surfaces and gold connector(s) all surfacesanodize cover all surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A158a0