

View Online at <https://aerobasegroup.com/nsn/5985-01-369-6517>

Body Style:

Rectangular

Overall Length:

1.500 inches

Overall Height:

1.500 inches

Overall Width:

0.780 inches

Frequency Rating:

20.0 megahertz single frequency operating and 300.0 megahertz single frequency operating

Unthreaded Mounting Hole Diameter:

0.093 inches

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.336 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.336 inches single mounting facility pattern

Voltage Standing Wave Ratio:

1.25 single

Insertion Loss In Decibels:

0.70 single

Coaxial Connector Series Designation:

Sma

Minimum Crosstalk Rating In Decibels:

55.0 single

Actuator Operating Method:

Manual

Actuator Current Type And Rating In Amps:

Between 0.05 dc and 0.06 dc

Switch Operation Sequence:

Breaks before makes

Switching Time:

4.0 microseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Aluminum alloy 6063 bodycopper alloy contact (s)

Precious Material And Location:

Body surfaces silver and contact surfaces gold

Precious Material:

Silver and gold

Surface Treatment:

Paint body all surfaces and silver body all surfaces and nickel body all surfaces and copper body all surfacesgold contact (s) all surfaces

Terminal Type And Quantity:

2 wire lead and 3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A158a0