NSN 5985-01-369-6991

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-369-6991

| Application Design: |
|--|
| Transmission line |
| Body Material: |
| Steel, stainless |
| Body Style: |
| Err-090 |
| Body Surface Treatment: |
| Passivated |
| Overall Length: |
| 0.860 inches |
| Overall Diameter: |
| 0.280 inches |
| Operating Tempurature Range: |
| -65.0/+125.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.15 |
| Coaxial Connector Series Designation: |
| Sma |
| Power Rating: |
| 2.0 watts average |
| Rf Signal Attenuation In Decibels: |
| 10.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +1.0/+2.0 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.30/+0.30 |
| Connection Type Per Function: |
| Male input and female output |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 1.000 gigahertz and 2.000 gigahertz |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |

A20000