NSN 5985-01-369-9670

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-369-9670

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.275 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.075 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.350 inches
Overall Height:
0.510 inches
Overall Width:
2.130 inches
Unthreaded Mounting Hole Diameter:
0.116 inches
Voltage Standing Wave Ratio:
2.00
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+0.5
-
+0.0/+0.5
+0.0/+0.5 Attenuation Variation Method:
+0.0/+0.5 Attenuation Variation Method: Continuous
+0.0/+0.5 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity:
+0.0/+0.5 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole
+0.0/+0.5 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range: Between 1150.000 megahertz and 1450.000 megahertz
+0.0/+0.5 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range:
+0.0/+0.5 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range: Between 1150.000 megahertz and 1450.000 megahertz Adjustment Device Type And Quantity:
+0.0/+0.5 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range: Between 1150.000 megahertz and 1450.000 megahertz Adjustment Device Type And Quantity: 1 slotted screw
+0.0/+0.5 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range: Between 1150.000 megahertz and 1450.000 megahertz Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern:
+0.0/+0.5 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range: Between 1150.000 megahertz and 1450.000 megahertz Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern: Four position rectangular
Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range: Between 1150.000 megahertz and 1450.000 megahertz Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern: Four position rectangular Terminal Type And Quantity:
Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole Frequency Range: Between 1150.000 megahertz and 1450.000 megahertz Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern: Four position rectangular Terminal Type And Quantity: 2 connector, coaxial, female

--

NSN 5985-01-369-9670

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0